


# TK 10 BG

Transformer terminal, screw connection, mounting type: special profiles, rated cross-section: 4 mm<sup>2</sup>, width: 9 mm, colour: beige

|                                                                                                                                                                                                                                                      |           |                                                                                     |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|-------------------------------------------------------------------------------------|
| Item number:                                                                                                                                                                                                                                         | 1138.4    |  |
| Product weight (kg):                                                                                                                                                                                                                                 | 0.0152 kg |                                                                                     |
| Packing unit:                                                                                                                                                                                                                                        | 50        |                                                                                     |
|    |           |                                                                                     |

## TECHNICAL CHARACTERISTICS

|                                                          |                  |
|----------------------------------------------------------|------------------|
| Connection type:                                         | Screw connection |
| Series:                                                  | TK               |
| Number of poles:                                         | 1                |
| Rated cross-section (mm <sup>2</sup> ):                  | 4                |
| Rated current (A):                                       | 32               |
| Rated voltage (VDC):                                     | 800              |
| Wire section AWG:                                        | 22 - 10          |
| Cross-section rigid (mm <sup>2</sup> ):                  | 0.2 - 10         |
| Flexible conductor cross-section (mm <sup>2</sup> ):     | 0.2 - 10         |
| Conductor cross section with ferrule (mm <sup>2</sup> ): | 0.2 - 10         |
| Material:                                                | Polyamide PA6.6  |
| Colour:                                                  | Black            |
| Thread:                                                  | M4               |

## TECHNICAL CHARACTERISTICS

|                              |                                    |
|------------------------------|------------------------------------|
| Tightening torque min. (Nm): | 1.2                                |
| Tightening torque max. (Nm): | 2                                  |
| Flammability rating UL 94:   | V0                                 |
| UL test standard:            | UL 1059                            |
| UL file number:              | E95701                             |
| ROHS compliant:              | Yes                                |
| REACH compliant:             | Yes                                |
| Manufacturer:                | CONTA-CLIP Verbindungstechnik GmbH |

## DIMENSIONS

|              |      |
|--------------|------|
| Length (mm): | 40.5 |
| Width (mm):  | 9    |