


TK 4/5 BG

Transformer terminal, screw connection, mounting type: special profiles, rated cross-section: 4 mm², width: 7.5 mm, colour: beige

Item number: 1145.3 Product weight (kg): 0.0198 kg Packing unit: 10	
UL94 V-0 E95701 RoHS REACH	

TECHNICAL CHARACTERISTICS

Connection type:	Screw connection
Series:	TK
Number of poles:	5
Rated cross-section (mm ²):	4
Rated current (A):	32
Rated voltage (VDC):	800
Wire section AWG:	22 - 10
Cross-section rigid (mm ²):	0.2 - 6
Flexible conductor cross-section (mm ²):	0.2 - 6
Conductor cross section with ferrule (mm ²):	0.2 - 4
Material:	Polyamide PA6.6
Colour:	Orange

TECHNICAL CHARACTERISTICS

Thread:	M3
Tightening torque min. (Nm):	0.5
Tightening torque max. (Nm):	1
Flammability rating UL 94:	V0
UL test standard:	UL 1059
UL file number:	E95701
ROHS compliant:	Yes
REACH compliant:	Yes
Manufacturer:	CONTA-CLIP Verbindungstechnik GmbH

DIMENSIONS

Length (mm):	20.5
Width (mm):	7.5