

# TK 4/5/F BG

Transformer terminal, screw connection + flat plug connection, mounting type: special profiles, rated cross-section: 4 mm², width: 7.5 mm, colour: beige

Item number: 1155.3

Product weight (kg): 0.0252 kg

Packing unit: 10



## TECHNICAL CHARACTERISTICS

|                                             |                                              |
|---------------------------------------------|----------------------------------------------|
| Connection type:                            | Screw connection + blade terminal connection |
| Series:                                     | TK                                           |
| Number of poles:                            | 5                                            |
| Rated cross-section (mm²):                  | 4                                            |
| Rated current (A):                          | 32                                           |
| Rated voltage (VDC):                        | 800                                          |
| Wire section AWG:                           | 22 - 10                                      |
| Cross-section rigid (mm²):                  | 0.2 - 6                                      |
| Flexible conductor cross-section (mm²):     | 0.2 - 6                                      |
| Conductor cross section with ferrule (mm²): | 0.2 - 4                                      |
| Material:                                   | Polyamide PA6.6                              |
| Colour:                                     | Orange                                       |
| Thread:                                     | M3                                           |
| Tightening torque min. (Nm):                | 0.5                                          |
| Tightening torque max. (Nm):                | 1                                            |
| Spade terminal connection:                  | 6.3/2 x 2.8 x 0.8                            |
| Flammability rating UL 94:                  | V0                                           |
| UL test standard:                           | UL 1059                                      |
| UL file number:                             | E95701                                       |
| ROHS compliant:                             | Yes                                          |
| REACH compliant:                            | Yes                                          |
| Manufacturer:                               | CONTA-CLIP Verbindungstechnik GmbH           |

## DIMENSIONS



## DIMENSIONS

|              |      |
|--------------|------|
| Length (mm): | 27.8 |
| Width (mm):  | 7.5  |