

TK 4/6/F OG

Transformer terminal, screw connection + flat plug connection, mounting type: special profiles, rated cross-section: 4 mm², width: 7.5 mm, colour: orange

Item number: 1156.2

Product weight (kg): 0.0302 kg


Packing unit: 10



TECHNICAL CHARACTERISTICS

Connection type:	Screw connection + blade terminal connection
Series:	TK
Number of poles:	6
Rated cross-section (mm²):	4
Rated current (A):	32
Rated voltage (VDC):	800
Wire section AWG:	22 - 10
Cross-section rigid (mm²):	0.2 - 6
Flexible conductor cross-section (mm²):	0.2 - 6
Conductor cross section with ferrule (mm²):	0.2 - 4
Material:	Polyamide PA6.6
Colour:	Beige
Thread:	M3
Tightening torque min. (Nm):	0.5
Tightening torque max. (Nm):	1
Spade terminal connection:	6.3/2 x 2.8 x 0.8
Flammability rating UL 94:	V0
UL test standard:	UL 1059
UL file number:	E95701
ROHS compliant:	Yes
REACH compliant:	Yes
Manufacturer:	CONTA-CLIP Verbindungstechnik GmbH

DIMENSIONS



DIMENSIONS

Length (mm):	27.8
Width (mm):	7.5