

DATASHEET

Order number: 12124

DESCRIPTION

- Patented LockEX pressure relief system
- System with flexible network capability – communication via Wi-Fi or SMS for maximum availability, even without an internet connection



lockEX[®]2.0
inside

TECHNICAL DATA

External dimensions (lxwxh)	89 x 66 x 115 cm
Internal dimensions (lxwxh)	73 x 53 x 91 cm
Weight	152 kg
VDMA Certification	I
TÜV Nord Certification	44 780 23136701
Installation Location	indoor
Material	non-combustible building material
Coating	HPL (high pressure laminate)
Container Colour	grey
Door Colour	orange
Operating Voltage	230 V

Maximum power	3500 W (16 A)
Frequency	50/60 Hz
Fan Noise Level	33
Permissible Energy	6320 Wh
Load Capacity per Storage Level	30 kg / Level
Stackable	no
Forkliftable	yes
Permissible Energy Per Storage Level	1580 Wh
Assembly condition	mounted
Plug	protective contact

EQUIPMENT

Feet/Castors	castors
Number of Doors	2
Door Model	double hinged doors
Door Lock Type	T-handle with 2 point locking
Mechanical Ventilation	yes
Door Contact Switch	yes
Number of Power Sockets	2x9
Volt-Free Contact	yes
Storage Levels	4
Number of Shelves	3
Shelf Material	powder-coated steel
Smoke Detector	<p>electric</p>
Temperature Detection	temperature sensor
Display	yes
Warning Signal	<p>audible</p>
Alarm Transmission	yes

SUITABLE MEDIA

Lithium Battery

LOGISTICS

Package dimensions (lwxhx)	120 x 80 x 130 cm
Pallet Dimensions	120 x 80 x 130 cm
Package Weight	174 kg

APPROVAL



ACCESSORIES



11345 -



11389 -



11561 -

[Link to product](#)

