

TKS 4/3/F RD

Transformer terminal, screw connection + flat plug connection, mounting type: special profiles, rated cross-section: 4 mm², width: 22.5 mm, colour: red

Item number:	1227.8
Product weight (kg):	0.015 kg
Packing unit:	20



TECHNICAL CHARACTERISTICS

Connection type:	Screw connection + blade terminal connection
Series:	TKS
Number of poles:	3
Rated cross-section (mm²):	4
Rated current (A):	32
Rated voltage (VDC):	800
Wire section AWG:	22 - 10
Cross-section rigid (mm²):	0.2 - 6
Flexible conductor cross-section (mm²):	0.2 - 6
Conductor cross section with ferrule (mm²):	0.2 - 4
Material:	Polyamide PA6.6
Colour:	Green-yellow

TECHNICAL CHARACTERISTICS

Thread:	M3
Tightening torque min. (Nm):	0.5
Tightening torque max. (Nm):	1
Spade terminal connection:	6.3/2 x 2.8 x 0.8
Flammability rating UL 94:	V0
ROHS compliant:	No
REACH compliant:	No
Manufacturer:	CONTA-CLIP Verbindungstechnik GmbH

DIMENSIONS

Length (mm):	27.7
Width (mm):	22.5