

# PRSU 4G/115V AC

Pre-assembled relay module PRS..., screw connection, consisting of: Relay socket, power contact relay, pluggable display/interference suppression module and retaining bracket, 4 changeover contacts, input voltage: 115 VAC


|                      |           |
|----------------------|-----------|
| Item number:         | 15733.2   |
| Product weight (kg): | 0.0554 kg |
| Packing unit:        | 1         |



## TECHNICAL CHARACTERISTICS

|                                                 |                                    |
|-------------------------------------------------|------------------------------------|
| Series:                                         | PRS                                |
| Connection type:                                | Screw connection                   |
| Rated cross-section (mm²):                      | 1.5                                |
| Rated current (A):                              | 6                                  |
| Input voltage (VAC):                            | 115                                |
| Flexible conductor cross-section (mm²):         | 0.2 - 1.5                          |
| Switching voltage / switching voltage max. (V): | 240 / 240                          |
| Contact configuration:                          | 4 changeover contacts              |
| Contact Material:                               | AgNi 90/10                         |
| REACH compliant:                                | Yes                                |
| ROHS compliant:                                 | Yes                                |
| Manufacturer:                                   | CONTA-CLIP Verbindungstechnik GmbH |

## DIMENSIONS



## DIMENSIONS

|                 |      |
|-----------------|------|
| Length (mm):    | 76   |
| Width (mm):     | 27.1 |
| Height TS (mm): | 87   |