

# PRSU 1Z/60V DC

Pre-assembled relay module PRS..., spring-loaded connection, consisting of: relay socket, power contact relay, pluggable display/interference suppression module and retaining bracket, 1 changeover contact, input voltage: 60 VDC

Item number: 15783.2

Product weight (kg): 0.0554 kg


Packing unit: 1



## TECHNICAL CHARACTERISTICS

|                                                      |                                    |
|------------------------------------------------------|------------------------------------|
| Series:                                              | PRS                                |
| Connection type:                                     | Tension spring connection          |
| Rated cross-section (mm <sup>2</sup> ):              | 1                                  |
| Rated current (A):                                   | 12                                 |
| Input voltage (VDC):                                 | 60                                 |
| Flexible conductor cross-section (mm <sup>2</sup> ): | 0.2 - 1                            |
| Switching voltage / switching voltage max. (V):      | 250 / 400                          |
| Contact configuration:                               | 1 changeover contact               |
| Contact Material:                                    | AgNi 90/10                         |
| REACH compliant:                                     | Yes                                |
| ROHS compliant:                                      | Yes                                |
| Manufacturer:                                        | CONTA-CLIP Verbindungstechnik GmbH |

## DIMENSIONS



## DIMENSIONS

|                 |      |
|-----------------|------|
| Length (mm):    | 98   |
| Width (mm):     | 16.3 |
| Height TS (mm): | 69.2 |