

# PRSU 4/24V DC Au

Pre-assembled relay module PRS..., screw connection, consisting of: relay base, relay with multi-layer gold contact, plug-in indicator/interference suppression module and retaining bracket, 4 changeover contacts, input voltage: 24 VDC

|                      |           |
|----------------------|-----------|
| Item number:         | 16127.2   |
| Product weight (kg): | 0.0886 kg |
| Packing unit:        | 5         |



## TECHNICAL CHARACTERISTICS

|                                                 |                                    |
|-------------------------------------------------|------------------------------------|
| Series:                                         | PRS                                |
| Connection type:                                | Screw connection                   |
| Rated cross-section (mm²):                      | 1.5                                |
| Rated current (A):                              | 6                                  |
| Input voltage (VDC):                            | 24                                 |
| Flexible conductor cross-section (mm²):         | 0.2 - 1.5                          |
| Switching voltage / switching voltage max. (V): | 240 / 240                          |
| Contact configuration:                          | 4 changeover contacts              |
| Contact Material:                               | AgNi 90/10 + Au                    |
| REACH compliant:                                | Yes                                |
| ROHS compliant:                                 | Yes                                |
| Manufacturer:                                   | CONTA-CLIP Verbindungstechnik GmbH |

## DIMENSIONS

|                 |      |
|-----------------|------|
| Length (mm):    | 76   |
| Width (mm):     | 27.1 |
| Height TS (mm): | 85   |