


# IRCPU 1/240V AC

Interface relay compact (IRC) Complete, consisting of IRCP... base with screw connection and pluggable miniature relay PRC... with power contact, mounting type: TS 35, 1 changeover contact, input voltage: 240 VAC

|                      |           |
|----------------------|-----------|
| Item number:         | 16240.2   |
| Product weight (kg): | 0.0411 kg |
| Packing unit:        | 10        |



## TECHNICAL CHARACTERISTICS

|                                                 |                      |
|-------------------------------------------------|----------------------|
| Series:                                         | IRC                  |
| Connection type:                                | Screw connection     |
| Rated cross-section (mm²):                      | 2.5                  |
| Rated current (A):                              | 6                    |
| Input voltage (VAC):                            | 220 - 240            |
| Flexible conductor cross-section (mm²):         | 0.2 - 2.5            |
| Switching voltage / switching voltage max. (V): | 230 / 400            |
| Contact configuration:                          | 1 changeover contact |
| UL test standard:                               | UL 508               |

## TECHNICAL CHARACTERISTICS

CSA No.: CSA-C22.2 No. 14

REACH compliant: Yes

ROHS compliant: Yes

Manufacturer: CONTA-CLIP Verbindungstechnik GmbH

## DIMENSIONS

Length (mm): 94.3

Width (mm): 6.2

Height TS (mm): 90.7