


# PRK 6/2A BK

Feed-through terminal block, push-in connection, mounting type: TS 35/7.5, rated cross-section: 6 mm<sup>2</sup>, width: 8.1 mm, colour: black

|                      |           |
|----------------------|-----------|
| Item number:         | 27018.4   |
| Product weight (kg): | 0.0126 kg |
| Packing unit:        | 50        |



## TECHNICAL CHARACTERISTICS

|                                                          |               |
|----------------------------------------------------------|---------------|
| Series:                                                  | PRK           |
| Connection type:                                         | Push-in       |
| Rated cross-section (mm <sup>2</sup> ):                  | 6             |
| Rated current (A):                                       | 41            |
| Rated voltage (VDC):                                     | 1000          |
| Number of cables:                                        | 2             |
| Cross-section rigid (mm <sup>2</sup> ):                  | 0.5-10        |
| Flexible conductor cross-section (mm <sup>2</sup> ):     | 0.5-6         |
| Conductor cross section with ferrule (mm <sup>2</sup> ): | 0.5-6         |
| Wire section AWG:                                        | 20 - 8        |
| Shell material:                                          | Polyamide 6.6 |
| Colour:                                                  | Black         |

## TECHNICAL CHARACTERISTICS

|                   |                                    |
|-------------------|------------------------------------|
| UL test standard: | UL 1059                            |
| UL file number:   | E95701                             |
| ROHS compliant:   | Yes                                |
| REACH compliant:  | Yes                                |
| Manufacturer:     | CONTA-CLIP Verbindungstechnik GmbH |

## DIMENSIONS

|                 |      |
|-----------------|------|
| Length (mm):    | 57.7 |
| Width (mm):     | 8.1  |
| Height TS (mm): | 44   |