


# KDS-DE 2X4-5 GR

Seal, length x width: 20.3 mm, cable diameter max.: 5 mm

Item number: 28595.6


Packing unit: 10



## TECHNICAL CHARACTERISTICS

|                                |                                    |
|--------------------------------|------------------------------------|
| Material:                      | TPE                                |
| UV-stabilised:                 | No                                 |
| Halogen-free:                  | Yes                                |
| Silicone-free:                 | Yes                                |
| Colour:                        | Grey                               |
| Mounting type:                 | Pluggable                          |
| Working temperature min. (°C): | -40°C                              |
| Working temperature max. (°C): | +90°C                              |
| Flammability rating UL 94:     | V0                                 |
| UL test standard:              | UL 508A                            |
| UL file number:                | E489821                            |
| Protection class:              | IP66                               |
| Strain relief:                 | Yes                                |
| Number of cables:              | 2                                  |
| Cable diameter min. (mm):      | 4                                  |
| Cable diameter max. (mm):      | 5                                  |
| ROHS compliant:                | Yes                                |
| REACH compliant:               | Yes                                |
| Manufacturer:                  | CONTA-CLIP Verbindungstechnik GmbH |

## DIMENSIONS



## DIMENSIONS

|              |      |
|--------------|------|
| Width (mm):  | 20.3 |
| Height (mm): | 17.7 |
| Length (mm): | 20.3 |