

# KDS-DE 4X5 GR

Seal, length x width: 20.3 mm, cable diameter max.: 5 mm

Item number: 28673.6  
Packing unit: 10



## TECHNICAL CHARACTERISTICS

|                                |           |
|--------------------------------|-----------|
| Material:                      | TPE       |
| UV-stabilised:                 | No        |
| Halogen-free:                  | Yes       |
| Silicone-free:                 | Yes       |
| Colour:                        | Grey      |
| Mounting type:                 | Pluggable |
| Working temperature min. (°C): | -40       |
| Working temperature max. (°C): | +90       |
| Flammability rating UL 94:     | V0        |
| UL test standard:              | UL 508A   |
| UL file number:                | E489821   |
| Protection class EN 60529:     | IP66      |
| Strain relief:                 | Yes       |

## TECHNICAL CHARACTERISTICS

|                           |                                    |
|---------------------------|------------------------------------|
| Number of cables:         | 4                                  |
| Cable diameter min. (mm): | 4.7                                |
| Cable diameter max. (mm): | 5.1                                |
| ROHS compliant:           | Yes                                |
| REACH compliant:          | Yes                                |
| Manufacturer:             | CONTA-CLIP Verbindungstechnik GmbH |

## DIMENSIONS

|              |      |
|--------------|------|
| Width (mm):  | 20.3 |
| Height (mm): | 17.7 |
| Length (mm): | 20.3 |