

# KDS-RGA M20 BK

Thread and locking adapter

Item number: 28771.4


Packing unit: 5



## TECHNICAL CHARACTERISTICS

|                                |                                    |
|--------------------------------|------------------------------------|
| Material:                      | Polyamide PA6.6                    |
| Glass fibre reinforced:        | Yes                                |
| Halogen-free:                  | Yes                                |
| Silicone-free:                 | Yes                                |
| Colour:                        | Black                              |
| Mounting type:                 | Screw                              |
| Working temperature min. (°C): | -40                                |
| Working temperature max. (°C): | +120                               |
| Flammability rating UL 94:     | V0                                 |
| UL test standard:              | UL 508A                            |
| UL file number:                | E489821                            |
| Protection class EN 60529:     | IP66                               |
| ROHS compliant:                | Yes                                |
| REACH compliant:               | Yes                                |
| Manufacturer:                  | CONTA-CLIP Verbindungstechnik GmbH |

## DIMENSIONS



## DIMENSIONS

|                           |      |
|---------------------------|------|
| Width (mm):               | 38   |
| Height (mm):              | 22.1 |
| Construction height (mm): | 14.9 |
| Length (mm):              | 38   |
| Cut-out width (mm):       | 20.3 |
| Cut-out length (mm):      | 20.3 |