


KES-E-R 50/18 A GR

Round cable entry M50 with membrane for unassembled cables, Length: 60 mm, Width: 60 mm

Item number: 28833.6



Packing unit: 10



TECHNICAL CHARACTERISTICS

Material:	TPE
Halogen-free:	Yes
Silicone-free:	Yes
Sealing material:	TPE
Colour:	Grey
Mounting type:	Snap-on
Working temperature min. (°C):	-40
Working temperature max. (°C):	+90
Flammability rating UL 94:	V0
UL test standard:	UL 508A
UL file number:	E489821
Protection class EN 60529:	IP54
Number of cables:	18
Number of cables for cable diameter 1.0 - 7.2 mm:	4
Number of cables for cable diameter 1.0 - 12.0 mm:	5
Number of cables for cable diameter 1.0 - 6.0 mm:	2
Number of cables for cable diameter 1.0 - 4.0 mm:	2
Number of cables for cable diameter 1.0 - 9.4 mm:	5
ROHS compliant:	Yes
REACH compliant:	Yes
Manufacturer:	CONTA-CLIP Verbindungstechnik GmbH

DIMENSIONS



DIMENSIONS

Width (mm):	57.96
Height (mm):	12
Construction height (mm):	5
Length (mm):	57.96
Cut-out width (mm):	50
Cut-out length (mm):	50