

KES-E 18/24 B GR

Cable entry with membrane for unassembled cables, Sheet thickness 2.5 - 4 mm, Length: 142 mm, Width: 44 mm

Item number: 28843.6

Packing unit: 10



TECHNICAL CHARACTERISTICS

Material: TPE

Halogen-free: Yes

Silicone-free: Yes

Sealing material: TPE

TECHNICAL CHARACTERISTICS

Colour:	Grey
Mounting type:	Snap-on
Working temperature min. (°C):	-40
Working temperature max. (°C):	+90
Flammability rating UL 94:	V0
UL test standard:	UL 508A
UL file number:	E489821
Protection class EN 60529:	IP66
Number of cables:	18
Number of cables for Ø 1.0 - 12.5 mm:	5
Number of cables for Ø 1.0 - 6.5 mm:	4
Number of cables for Ø 1.0 - 16.1 mm:	4
Number of cables for Ø 1.0 - 10.5 mm:	5
ROHS compliant:	Yes
REACH compliant:	Yes
Manufacturer:	CONTA-CLIP Verbindungstechnik GmbH

DIMENSIONS

Width (mm):	44
Height (mm):	12
Construction height (mm):	5
Length (mm):	142
Cut-out width (mm):	36
Cut-out length (mm):	112