


KES-GB-FDA 14/24 BU

Cable entry with membrane for unassembled cables, Length: 147 mm, Width: 58 mm, FDA compliant

Item number: 28901.5


Packing unit: 10



TECHNICAL CHARACTERISTICS

Material:	Polyamide PA6.6
Material approval:	FDA-compliant elastomer according to food approval 1935/2004/EC and (EU) 10/2011
Glass fibre reinforced:	Yes
Halogen-free:	Yes
Silicone-free:	Yes
Sealing material:	TPE
Colour:	Blue
Mounting type:	Snap-on and screw-on
Number of screw holes:	4
Fastening screw torque (Nm):	3
Working temperature min. (°C):	-40°C
Working temperature max. (°C):	+90°C
Flammability rating UL 94:	HB
Protection class:	IP66
Number of cables:	14
Number of cables for cable diameter 12.0 - 16.2 mm:	3
Number of cables for cable diameter 8.0 - 12.5 mm:	1
Number of cables for cable diameter 5.5 - 10.5 mm:	3
Number of cables for cable diameter 4.0 - 7.5 mm:	3
Number of cables for cable diameter 3.2 - 6.3 mm:	5
ROHS compliant:	Yes
REACH compliant:	Yes
Manufacturer:	CONTA-CLIP Verbindungstechnik GmbH

DIMENSIONS



DIMENSIONS

Width (mm):	58
Construction height (mm):	14.5
Length (mm):	149.5
Cut-out width (mm):	36
Cut-out length (mm):	112