


# FSL 4/2A GNYE

Protective conductor terminal, push-in connection, mounting type: TS 35/7.5, rated cross-section: 4 mm<sup>2</sup>, width: 6.1 mm, colour: green-yellow

|                      |           |
|----------------------|-----------|
| Item number:         | 3223.2    |
| Product weight (kg): | 0.0122 kg |
| Packing unit:        | 100       |



## TECHNICAL CHARACTERISTICS

|                                                          |               |
|----------------------------------------------------------|---------------|
| Series:                                                  | FRK           |
| Connection type:                                         | Push-in       |
| Rated cross-section (mm <sup>2</sup> ):                  | 4             |
| Number of cables:                                        | 2             |
| Cross-section rigid (mm <sup>2</sup> ):                  | 0.2-6         |
| Flexible conductor cross-section (mm <sup>2</sup> ):     | 0.2-6         |
| Conductor cross section with ferrule (mm <sup>2</sup> ): | 0.2-4         |
| Wire section AWG:                                        | 20 - 10       |
| Shell material:                                          | Polyamide 6.6 |
| Colour:                                                  | Green-yellow  |

## TECHNICAL CHARACTERISTICS

|                  |                                    |
|------------------|------------------------------------|
| CSA No.:         | C22.2 No 158                       |
| ROHS compliant:  | Yes                                |
| REACH compliant: | Yes                                |
| Manufacturer:    | CONTA-CLIP Verbindungstechnik GmbH |

## DIMENSIONS

|                 |      |
|-----------------|------|
| Length (mm):    | 48.5 |
| Width (mm):     | 6.1  |
| Height TS (mm): | 43   |