

# Wire end sleeve pre insulated, DIN 46228 T4, 1.0mm<sup>2</sup>

Type AH, for fine-stranded copper wires, reel

Item number: AH-005717  
Packing unit: 3000




## TECHNICAL CHARACTERISTICS

|                         |                    |
|-------------------------|--------------------|
| Wire section (mm²):     | 1                  |
| Wire section (AWG/MCM): | 18                 |
| Length (mm):            | 8                  |
| Isolated:               | Yes                |
| Insulation material:    | Polypropylene (PP) |
| Colour:                 | Red                |
| Material:               | Copper             |
| Surface:                | tin plated         |
| Max. temperature (°C):  | +105               |
| UL 486F No.:            | E485383            |

## TECHNICAL CHARACTERISTICS

|               |                  |
|---------------|------------------|
| CSA No.:      | 242724           |
| Standards:    | DIN 46228 T4     |
| Manufacturer: | GLW GmbH         |
| Packing:      | On reels Ø 250mm |

## DIMENSIONS



## DIMENSIONS

|          |      |
|----------|------|
| d1 (Ø):  | 1.5  |
| d2 (Ø):  | 3.0  |
| L1 (mm): | 14.5 |
| L2 (mm): | 8.0  |
| R1 (mm): | 3.9  |