

CEMO Battery charging cabinet Basic 8/20, 230 V with feet

Item number: CEMO-12048CH
 Product weight (kg): 267 kg
 Packing unit: 1



Fire- and explosion-resistant safety cabinet, specifically designed for the storage and charging of lithium-ion batteries.

Basic model, certified in accordance with VDMA Standard Sheet 24994:2024-08, Chapter 4.3.

Safe storage and charging of lithium-ion batteries up to 12 kWh – ideal for applications with high energy requirements.

Maximum safety in the event of a fire – withstands a battery fire and ensures no escape of flames or sparks.

Efficient layout and clear compartmentalisation through two areas that can be opened independently of one another.

Patent-protected LockEX pressure relief system.

Fire-retardant storage levels – prevent the spread of fire between individual battery modules.

User-friendly and cost-effective – the cost-efficient solution that focuses on the essentials.



TECHNICAL CHARACTERISTICS

| | |
|--|----------------------------|
| Power supply: | 230 |
| Connection type: | Typ 13 |
| Maximum electrical power (W): | 2300 |
| Current (A): | 10 |
| Number of sockets: | 4x 9 |
| Permissible total energy (Wh): | 12640 |
| Permissible energy per storage level (Wh): | 1580 |
| Smoke detector: | Battery-powered |
| Temperature measurement: | Thermal fuse |
| Display: | No |
| Warning signal: | Acoustic |
| Alarm forwarding: | No |
| Potential-free contact: | No |
| Storage levels: | 8 |
| Number of shelves / special cushions: | 6 |
| Stackable: | No |
| Feet/Castors: | With stacking feet |
| Under-rideable: | Yes |
| Certificate acc. to VDMA 24994:2024-08: | VDMA 24994 44 780 23136701 |
| Manufacturer: | CEMO |

DIMENSIONS

| | |
|-------------|------------------|
| LxWxH (mm): | 800 x 660 x 2130 |
|-------------|------------------|