

# Polyamide PA6.6 insulated terminal CU, 4 - 6mm<sup>2</sup>

Type KY, for copper conductors, fork/spade terminal

|                                                                                                                                                                                                                                                      |          |                                                                                     |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|-------------------------------------------------------------------------------------|
| Item number:                                                                                                                                                                                                                                         | GKY-U3.5 |  |
| Packing unit:                                                                                                                                                                                                                                        | 100      |                                                                                     |
|    |          |                                                                                     |

## TECHNICAL CHARACTERISTICS

|                                  |                         |
|----------------------------------|-------------------------|
| Material:                        | ETP copper (CW004A)     |
| Surface:                         | Elektrolytically tinned |
| Wire section (mm <sup>2</sup> ): | 4 - 6                   |
| Wire section (AWG/MCM):          | 12 - 10                 |
| Bolt (Ø):                        | 3.5                     |
| Colour:                          | Yellow                  |
| Operating temperature (°C):      | -20 - +105              |
| Max. temperature (°C):           | +110                    |
| Manufacturer:                    | Cembre S.p.A.           |

## DIMENSIONS



## DIMENSIONS

|          |      |
|----------|------|
| L1 (mm): | 24.4 |
| L2 (mm): | 3.9  |
| L3 (mm): | 7.5  |
| B1 (mm): | 7.2  |
| d1 (Ø):  | 7.0  |
| d2 (Ø):  | 3.7  |